DAKSH ENTERPRISES

FUNCTION AND FEATURES :

Sc-5500S

1. Adopting thermal foam inkjet microburst technology, which makes high picture quality.
2. The main body is made of aluminium alloy, more attractive and stronger, walking media axis is made of bearing steel-walking media more accurately.
3. Blue LCD in low-radiation, key-press with perfect design, which makes it very convenient to work at night and easier to operate.
4. Automatic media feeding and take-up system and automatic media cutter, make it convenient in application.
5. Upgraded mainboard with higher quality chips makes higher image quality; USB and paralleled printing ports give you more convenience.

TECHNICAL PARAMETERS :

Print Technology	On-demand thermal foam inkjet Microburst technology	Drivers	Windows95/98/Nt/2000/2003/XP/Vista
Ink Delivery System	Continuous ink system with refillable reservoirs	Output	Main Top
Max Printing Size	152cm, 60"	Interfaces	100 base T Ethernet option; IEEE 1284 Bi-tronics ECP(Extended Capability Port) Parallel
Colors	C M Y K	Processor	Power PC
Applied Ink	Sky-Color series dye-based and pigment-based ink	Buffer	32MB standard, expandable to 64 MB (2SIMM slots)
Applied Media	Indoor printing medias are compatible	Power Supply	Universal 90 to 264 VAC,47 to 63 HZ
Media Handling	Standard automated media feeding & take-up system on-board dryer, media cutter	Power Consumption	35W idle, 145W typical, 275W maximum
Print Resolution	600 x 600dpi; 300 x 300dpi	Noise	Standby: <60 DBA, operational:<72 DBA
File Resolution	Accepts 600 x 600 or 300 x 300 dpi files	Operation Environment	Temp;- 59°F to 86°F(15°C to 30°C Humidity: 20% to 80% RH, non condensing
Storage	Temp;- 5°F to 140°F(-21°C to 60°C Humidity: 5% to 80% RH, non condensing	Authentication	UL ,FCC ,CSA , TUV , CE Mark , ISO9001 : 2000
Language Options	English, French, Spanish, Italian,Portuguese Simplified Chinese, Traditional Chinese, Korean, Japanese	Weight	67Kg
		Dimensions	255cm x 71cm x 112cm

Standard Print Speed 600 dpi Output in square feet per hours(square meters per hours) 600dpi with 60" media					
Draft Mode	1 Pass	104 sfph (9.4 smph)	Quality Mode	3 Pass	84 sfph (7.8 smph)
Production Mode	2 Pass	97 sfph (9.0 smph)	Photo Mode	4 Pass	63 sfph (5.9 smph)